


Phaser® 3250 A4 Black and White Laser Printer Compact, business-ready productivity

This powerful little printer is ready to support a single user or a small workgroup with fast, automatic two-sided printing, office-friendly convenience and outstanding overall value.





More performance for less

- Get work done fast, with a print speed of up to 28 ppm and a first-page-out time less than 8.5 seconds.
- Automatic two-sided printing saves valuable time and paper.
- A network configuration with both Windows, Mac and Linux compatibility – is truly business-ready.
- The 400 MHz processor ensures all jobs print quickly and accurately, even when they're loaded with graphics.

Convenience, flexibility

- A surprisingly small footprint makes it easy to position within quick reach.
- Standard 32 MB memory can expand to 160 MB for enhanced performance when your workload demands it.
- Add a second 250-sheet paper tray for a total capacity of 500 sheets.
- Print on custom sizes and a wide range of media, from transparencies and card stock, to envelopes and postcards.
- Power Save and Toner Save modes help you spend less on electricity and consumables.

Always impressive results

- 600 x 600 dpi print resolution (up to 1200 x 1200 enhanced image quality) adds visual impact to important jobs.
- PostScript[®] 3[™] compatibility* and PCL[®] 6 emulation ensure your print jobs are always accurate.
- A 30,000-page monthly duty cycle handles big print volumes with ease.
- Outstanding Xerox quality, reliability and performance are backed by Xerox Service and Support with a standard one-year on-site warranty with optional service extensions.

^{*} available on DN configuration only

Phaser® 3250

Black and white laser printer





		Phaser® 3250D	Phaser® 3250DN
Speed		Up to 28 ppm	
Duty Cycle		Up to 30,000 pages / month	
Paper Handling Paper input Standard		Bypass Tray: 1 sheet; Custom sizes: 76 x 127 mm to 216 x 356 mm Tray 1: 250 sheets; Sizes: A6 – A4	
	Optional	Tray 2: 250 sheets; Sizes: A6 – A4	
Paper output		150 sheets	
Automatic two-sided output		Standard	
Print First-page-out-time		As fast as 8	.5 seconds
Resolution		600 x 600 dpi (up to 1200 x 1200 enhanced image quality)	
Processor		400 MHz	
Memory (std/max)		32 MB / 160 MB	
Connectivity		USB 2.0	10/100Base-TX Ethernet, USB 2.0
Language support		PCL® 6 and 5e emulations, IBM Pro Printer emulation, Epson emulation, GDI	PostScript® 3" compatibility, PCL® 6 and 5e emulations, IBM ProPrinter emulation, Epson emulation, GDI
Print features		Watermarks, Poster printing, N-up, Fit to page, Scaling, Overlays, Booklets, Reduce/enlarge, Toner saver, Custom-size pages	
Warranty		One-year on-site warranty. Plus optional service extensions available.	

Device Management

Printer Setting Utility for Windows, 3250DN adds: CentreWare® Internet Services, SNMP 1-2, Ethertalk, HTTP, TCP/IP (DN configuration)

Print Drivers

Windows® 2000/XP/7/Server 2003/2008/Vista, Mac OS® X version 10.3-10.5, Various Linux® OS including SUSE™ 8.2-9.2, Red Hat® 8-9, Fedora™ Core 1-4, Mandrake 9.2-10.1

Font Support

1 bitmap, 45 scaleable, 136 PostScript® fonts

Media Handling

Multipurpose Tray: 60 – 163 gsm Media types: Plain paper, envelopes, transparencies, labels, card stock Tray 1 and Tray 2 (optional): 60 – 105 gsm Media types: Plain paper

Two sided printing: 75-90 gsmOperating Environment

Temperature: Storage: 0° to 35° C Operating: 10° to 32° C Humidity: 20% to 80% Sound pressure levels: Printing: 54 dB(A) Standby: 29 dB(A)

Warm-up time (from sleep mode): Less than 15 seconds

Power: 220-240 VAC, 50/60 Hz Power consumption: Standby: 70 W Printing: 400 W Power save: 11 W ENERGY STAR® qualified

Dimensions (WxDxH)

364 x 370 x 239 mm Weight: 11.9 kg Optional 250-sheet Tray 2: 364 x 400 x 86 mm Weight: 3.67 kg Package Dimensions (WxDxH): 562 x 472 x 344 mm

Listed UL 60950/CSA C22.2 No. 60950, CE Mark applicable to Directives 2006/95/EC and 2004/108/EC

What Comes In The Box

- Phaser 3250 Printer
- Print Cartridge (2,000 print capacity¹)
- Software and Documentation CD (with User Manual, Quick Installation Guide, Warranty Statement, Registration Card)
- Power cord

- USB cable



Phaser 3250 shown with optional Tray 2

Supplies

Standard-Capacity Print Cartridge¹:

3,500 std. pages 106R01373

High-Capacity Print Cartridge¹:

106R01374 5.000 std. pages

¹Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

Options

250-sheet Tray 098N02194 098N02195 128 MB Phaser Memory

Supplies Recycling Programme

Consumables for the Phaser 3250 are part of the Xerox Green World Alliance Supplies Recycling Programme. For more information, please visit the Green World Alliance website at www.xerox.com/gwa















